



como down

Design: IP44.de

Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h

Installation:
1 x Kabeleinführung
Anschlussklemme
3 x 2,5 mm²

Material:
Aluminium
Glaslinse

Schutzart:
IP65

EEK:




light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h

installation:
1 x cable entry point
connection terminal
3 x 2,5 mm²

material:
aluminium
glass lens

protection class:
IP65

EEC:



Größe in mm
size in mm

Art.-Nr.
item no.

Farbe
colour

Leistung
power

Lichtrichtung
light direction

90180-D



Aluminium
gebürstet, eloxiert
aluminium
brushed, anodized

7,5 W/610 lm



90180-D-AN



anthracite
RAL 7016

7,5 W/610 lm



90180-D-CB



cool brown

7,5 W/610 lm



IP44.de outside lighting

Marienstraße 13 . 33378 Rheda-Wiedenbrück . Germany
T +49 5242 5797-0 . F +49 5242 5797-10
welcome@IP44.de . www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.

IP44.de reserves the right to product adaptations at any time, without prior notice.