



**pip** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

dimmbar

**Installation:**  
1 x Kabeleinführung;  
Anschlussklemme  
3 x 2,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss  
ESG Glas klar

**Schutzart:**  
IP65

**EEK:**

light technology:  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h


dimmbare

installation:  
1 x cable entry point;  
connection terminal  
3 x 2,5 mm<sup>2</sup>

material:  
aluminium die-casting  
tempered safety glass clear

protection class:  
IP65

EEC:



Größe in mm  
size in mm

Art.-Nr. item no.	Farbe colour	Leistung power	Lichtrichtung light direction
91120-AN	anthracite RAL 7016	6 W/500 lm	
91120-CB	cool brown	6 W/500 lm	

**IP44.de outside lighting**

Marienstraße 13 . 33378 Rheda-Wiedenbrück . Germany  
T +49 5242 5797-0 . F +49 5242 5797-10  
welcome@IP44.de . www.IP44.de

**IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.**  
IP44.de reserves the right to product adaptations at any time, without prior notice.