






intro Design: IP44.de

| | | | |
|--|--|--|---|
| <p>Lichttechnik: 230V Power LED 3000K warmweiß L70/50.000 h</p> <p>dimmbar</p> <p>Installation: 2 x Kabeleinführung; Anschlussklemme 3 x 2,5 mm²</p> | <p>Material: Edelstahl Borosilikatglas satiniert</p> <p>Schutzart: IP65</p> <p>EEK: </p> | <p>light technology: 230V Power LED 3000K warm white L70/50.000 h</p> <p>dimmbare</p> <p>installation: 2 x cable entry point; connection terminal 3 x 2,5 mm²</p> | <p>material: stainless steel borosilicate glass satined</p> <p>protection class: IP65</p> <p>EEC: </p> |
|--|--|--|---|



Größe in mm
size in mm

| Art.-Nr. item no. | Farbe colour | Systemleistung system performance | Lichtrichtung light direction |
|----------------------|---|--------------------------------------|---|
| 90491 |  stainless steel | 10 W/360 lm |  |

IP44.de outside lighting
Mühlenstraße 20 . 33378 Rheda-Wiedenbrück . Germany
T +49 5242 5797-0 . F +49 5242 5797-10
welcome@IP44.de . www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.
IP44.de reserves the right to product adaptations at any time, without prior notice.