



cut Design: IP44.de

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

dimmbar

Installation:
2 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas klar

Schutzart:
IP65

EEK:

Lichtrichtung:



light technology:
230V Power LED
2700K + 3000K
L70/50.000 h

dimmable


installation:
2 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass clear

protection class:
IP65

EEC:

light direction:



Größe in mm
size in mm

| Farbe colour | 2700K ab from Q4/21 | | 3000K | |
|------------------------|----------------------|-----------------------------------|----------------------|-----------------------------------|
| | Art.-Nr. item no. | Systemleistung system perform. | Art.-Nr. item no. | Systemleistung system perform. |
| anthracite RAL 7016 | 91191-27-AN | 16W/996 lm | 91191-AN | 16 W/1078 lm |
| cool brown | 91191-27-CB | 16W/996 lm | 91191-CB | 16 W/1078 lm |
| space grey | 91191-27-SG | 16W/996 lm | 91191-SG | 16 W/1078 lm |
| pure white RAL 9016 | 91191-27-WH | 16W/996 lm | 91191-WH | 16 W/1078 lm |
| deep black RAL 9005 | 91191-27-BL | 16W/996 lm | 91191-BL | 16 W/1078 lm |