



pro S Design: IP44.de

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

Reflektor: Flood
dimmbar

Installation:
2 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas klar

Schutzart:
IP65

Lichtrichtung:


light technology:
230V Power LED
2700K + 3000K
L70/50.000 h


reflector: flood
dimmable






installation:
2 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass clear

protection class:
IP65

light direction:

Farbe colour	2700K 		3000K	
	Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
 anthracite RAL 7016	91810-27-S-AN	15 W/1099 lm	91810-S-AN	15 W/1150 lm
 space grey	91810-27-S-SG	15 W/1099 lm	91810-S-SG	15 W/1150 lm
 pure white RAL 9016	91810-27-S-WH	15 W/1099 lm	91810-S-WH	15 W/1150 lm
 deep black RAL 9005	91810-27-S-BL	15 W/1099 lm	91810-S-BL	15 W/1150 lm

Größe in mm
size in mm