



**in A . asymmetric** Design: IP44.de

für unbefestigte Beet- und Grünflächen

for unpaved beds and greens

**Lichttechnik:**  
230V Power LED  
2700K + 3000K  
L70/50.000 h

**Material:**  
**Abdeckring: Edelstahl**  
**Glas: Sicherheitsglas**  
**Gehäuse: Polyamid, Glasfaser verstärkt**

**light technology:**  
230V Power LED  
2700K + 3000K  
L70/50.000 h

**material:**  
cover ring: stainless steel  
glass: safety glass  
housing: polyamide, fibre glass reinforced

**Reflektor: Flood asymmetrisch**  
**dimmbar**

**Schutzart:**  
**IP67**

**reflector: flood asymmetric**  
**dimmbare**

**protection class:**  
**IP67**

**Installation:**  
2 m Anschlussleitung (H05RN8-F 3G0,75) mit Aquastop; Anschluss mehrerer Leuchten durch Sternverdrahtung mit externem Erd-Abzweigkasten möglich

**Lichtrichtung:**




**installation:**  
2 m connection cable (H05RN8-F 3G0,75) with aquastop; possibility of connection of several luminaires by star wiring with external earth distribution box

**light direction:**






**trittfest**

walk-over resistant



Größe in mm  
size in mm

Farbe colour		2700K 		3000K	
		Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
	stainless steel Sicherheitsglas klar safety glass clear	91081-27	8 W/ 539 lm	91081	8 W/540 lm
	stainless steel black galvanisiert Sicherheitsglas getönt galvanized safety glass tinted	91081-27-BL	8 W/238 lm	91081-BL	8 W/246 lm

+ Anschluss optional mit IP44.de connect.  
connection with IP44.de connect as an option.

Zubehör accessory	Artikel article	Art.-Nr. item no.
	<b>Erd-Abzweigkasten</b> earth distribution box	55380