



**intro** Design: IP44.de

**Lichttechnik:**  
230V Power LED  
2700K + 3000K  
L70/50.000 h

**dimmbar**

**Installation:**  
2 x Kabeleinführung;  
Anschlussklemme  
3 x 1,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Borosilikatglas satiniert

**Schutzart:**  
IP65

**EEK:**

**Lichtrichtung:**



light technology:  
230V Power LED  
2700K + 3000K  
L70/50.000 h

dimmable


installation:  
2 x cable entry point;  
connection terminal  
3 x 1,5 mm<sup>2</sup>

material:  
aluminium die-casting  
powder-coated  
borosilicate glass satined

protection class:  
IP65

EEC:

light direction:



Farbe colour	2700K  ab from Q3/21		3000K	
	Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
anthracite RAL 7016	92491-27-AN	15 W/451 lm	92491-AN	15 W/480 lm
cool brown	92491-27-CB	15 W/451 lm	92491-CB	15 W/480 lm
space grey	92491-27-SG	15 W/451 lm	92491-SG	15 W/480 lm
pure white RAL 9016	92491-27-WH	15 W/451 lm	92491-WH	15 W/480 lm
deep black RAL 9005	92491-27-BL	15 W/451 lm	92491-BL	15 W/480 lm

Größe in mm  
size in mm