




piek lettura connect Design: Sebastian David Büscher

piek lettura connect

Design: Sebastian David Büscher

Lichttechnik: 230V Power LED 2700K L70/50.000 h Reflektor: Flood Anschluss: 5m Zuleitung (H05RN8-F 3G0,75 mm²) inkl. connect Stecker 5 m Zuleitung auf Anfrage kürzbar [piek lettura controller: inkl. Controller] ortsveränderlich	Material: Kopf: Aluminiumguss pulverbeschichtet Stab: Edelstahl pulverbeschichtet Fuß: Eisenguss pulverbeschichtet Klarglas Schutzart: IP65  Lichtrichtung: 	light technology: 230V Power LED 2700K L70/50.000 h reflector: flood connection: 5m supply cable (H05RN8-F 3G0,75 mm²) incl. connect plug 5 m supply cable can be shortened on request [piek lettura controller: incl. controller] movable	material: head: aluminium die-casting powder-coated pole: stainless steel powder-coated base: iron casting powder-coated clear glass protection class: IP65  light direction: 
---	---	--	---

	Farbe colour	Art.-Nr. item no.	Systemleistung system performance
	 anthracite RAL 7016	92075-27-AN-CO	6 W/220 lm
	 cool brown	92075-27-CB-CO	6 W/220 lm
	 deep black RAL 9005	92075-27-BL-CO	6 W/220 lm

Größe in mm
size in mm