



**stic** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

**Reflektor:** Flood

**dimmbar**

**Installation:**  
2x Kabeleinführung;  
Anschlussklemme  
3x 1,5 mm<sup>2</sup>

**Material:**  
**Kopf:** Aluminiumguss  
pulverbeschichtet  
**Konsole:** Edelstahl  
pulverbeschichtet  
Sicherheitsglas klar

**Schutzart:**  
IP65



**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

**reflector:** flood

**dimmbable**


**installation:**  
2x cable entry point;  
connection terminal  
3x 1,5 mm<sup>2</sup>

**material:**  
head: aluminium die-casting  
powder-coated  
bracket: stainless steel  
powder-coated  
safety glass clear

**protection class:**  
IP65



**light direction:**



Größe in mm  
size in mm

**Farbe**  
colour

**Art.-Nr.**  
item no.

**Systemleistung**  
system performance



**anthracite**  
RAL 7016

91760-AN


8 W/559 lm



**cool brown**

91760-CB

8 W/559 lm



**pure white**  
RAL 9016

91760-WH

8 W/559 lm



**deep black**  
RAL 9005

91760-BL

8 W/559 lm