



piek lettura connect Design: Sebastian David Büscher

piek lettura connect Design: Sebastian David Büscher

Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: Flood
Abstrahlwinkel 38°

Anschluss:
3 m Zuleitung
(05RN8-F 3G0,75 mm²)
inkl. connect Stecker
Kabel auf Anfrage kürzbar

[piek lettura controller:
inkl. Controller]
ortsveränderlich

Material:
Kopf: Aluminiumguss
pulverbeschichtet
Stab: Edelstahl
pulverbeschichtet
Fuß: Eisenguss
pulverbeschichtet
Klarglas

Schutzart:
IP65



Lichtrichtung:

light technology:
230V Power LED
2700K
L70/50.000 h

reflector: flood
beam angle 38°

connection:
3 m supply cable
(05RN8-F 3G0,75 mm²)
incl. connect plug
supply cable can be
shortened on request


[piek lettura controller:
incl. controller]
movable

material:
head: aluminium die-casting
powder-coated
pole: stainless steel
powder-coated
base: iron casting
powder-coated
clear glass

protection class:
IP65



light direction:



Größe in mm
size in mm

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
anthracite RAL 7016	92075-27-AN-CO	6 W/220 lm
cool brown	92075-27-CB-CO	6 W/220 lm
deep black RAL 9005	92075-27-BL-CO	6 W/220 lm