




**como down** Design: IP44.DE



**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

**dimmbar über Phasenabschrittdimmer**

**dimmable via trailing edge dimmer**

**Installation:**  
1x Kabeleinführung; Anschlussklemme 3x 1,5 mm<sup>2</sup>

**installation:**  
1x cable entry point; connection terminal 3x 1,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss pulverbeschichtet + Glaslinse

**material:**  
aluminium die-casting powder-coated + glass lens

**Schutzart: IP65**

**protection class: IP65**






**Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G**

**This product contains a light source of energy efficiency class G**

**Lichtrichtung:**

**light direction:**



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	92181-27-AN	6 W/276 lm
 cool brown	92181-27-CB	6 W/276 lm
 space grey	92181-27-SG	6 W/276 lm
 pure white RAL 9016	92181-27-WH	6 W/276 lm
 deep black RAL 9005	92181-27-BL	6 W/276 lm

+ verwandte Produkte related products . como poller

Größe in mm  
size in mm