

mir X poller Design: Klaus Nolting

mir X poller Design: Klaus Nolting



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar über Phasenabschrittdimmer

Installation:
1x Kabeleinführung; Leitungsverbinder mit Anschlussklemme 3x 1,5 mm²
Anschluss mehrerer Leuchten durch Sternverdrahtung mit externem Erd-Abzweigkasten möglich

Montage:
bauseitiges Fundament oder befestigter Untergrund

Material:
Aluminiumguss pulverbeschichtet

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmable via trailing edge dimmer

installation:
1x cable entry point; cable connector with connection terminal 3x 1,5 mm²
possibility of connection of several luminaires by star wiring with external earth distribution box


assembly:
on site foundation or solid ground

material:
aluminium die-casting powder-coated


protection class: IP65

This product contains a light source of energy efficiency class G

light direction:



mir X 30 poller



mir X 70 poller

	Farbe colour		Art.-Nr. item no.	Systemleistung system performance
mir X 30 poller		anthracite RAL 7016	91001-27-AN	12 W/209 lm
		cool brown	91001-27-CB	12 W/209 lm
		deep black RAL 9005	91001-27-BL	12 W/209 lm
mir X 70 poller		anthracite RAL 7016	91002-27-AN	12 W/209 lm
		cool brown	91002-27-CB	12 W/209 lm
		deep black RAL 9005	91002-27-BL	12 W/209 lm

Zubehör accessory	Artikel article	Art.-Nr. item no.	
	Erd-Abzweigkasten earth distribution box	55380	Details . Seite page 256
	Erdstück anchorage unit	55099	Details . Seite page 256

+ verwandte Produkte related products . mir R poller

Größe in mm
size in mm