




up S Design: IP44.DE



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: Flood

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 1,5 mm²

Material:
Aluminiumguss pulverbeschichtet
+ Sicherheitsglas klar

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle
der Energieeffizienzklasse G

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

reflector: flood

dimmable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option

installation:
2x cable entry point; connection terminal 3x 1,5 mm²

material:
aluminium die-casting powder-coated
+ safety glass clear

protection class: IP65

This product contains a light source of
energy efficiency class G

light direction:



Farbe
colour



anthracite
RAL 7016

Art.-Nr.
item no.

91820-S-AN
91820-S-AN-DR . DALI-2 ready

Systemleistung
system performance

15 W/978 lm

pure white
RAL 9016

91820-S-WH
91820-S-WH-DR . DALI-2 ready

15 W/978 lm

deep black
RAL 9005

91820-S-BL
91820-S-BL-DR . DALI-2 ready

15 W/978 lm

+ verwandte Produkte related products . up R

Größe in mm
size in mm