

lisc



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 1,5 mm²

Material:
Aluminiumguss pulverbeschichtet
+ anthracite + pure white: Kristallglas, innen opalweiß
cool brown + deep black: rauchfarbenes Glas

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option


installation:
2x cable entry point; connection terminal 3x 1,5 mm²





material:
aluminium die-casting powder-coated
+ anthracite + pure white: crystal glass, opal white inside
cool brown + deep black: smoked glass

protection class: IP65

This product contains a light source of energy efficiency class G





light direction:




Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	91210-AN 91210-AN-DR . DALI-2 ready	14 W/815 lm
 pure white RAL 9016	91210-WH 91210-WH-DR . DALI-2 ready	14 W/815 lm
 cool brown	91210-CB 91210-CB-DR . DALI-2 ready	14 W/514 lm
 deep black RAL 9005	91210-BL 91210-BL-DR . DALI-2 ready	14 W/514 lm



lisc number

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	91210-NO-AN 91210-NO-AN-DR . DALI-2 ready	14 W/815 lm
 pure white RAL 9016	91210-NO-WH 91210-NO-WH-DR . DALI-2 ready	14 W/815 lm
 cool brown	91210-NO-CB 91210-NO-CB-DR . DALI-2 ready	14 W/514 lm
 deep black RAL 9005	91210-NO-BL 91210-NO-BL-DR . DALI-2 ready	14 W/514 lm



Größe in mm
size in mm