



slat bollard

slat bollard



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar über Phasenabschrittdimmer

Installation:
2x Kabeleinführung; Leitungsverbinder mit Anschlussklemme 3x 1,5 mm²
optional Durchgangsverdrahtung mit Y-Verbinder in der Leuchte möglich

Montage:
bauseitiges Fundament oder befestigter Untergrund

Material:
Aluminiumguss pulverbeschichtet
+ Sicherheitsglas satiniert

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmable via trailing edge dimmer

installation:
2x cable entry point; cable connector with connection terminal 3x 1,5 mm²
possibility of through wiring with Y-connector inside luminaire as an option


assembly:
on site foundation or solid ground

material:
aluminium die-casting powder-coated
+ safety glass satined


protection class: IP65

This product contains a light source of energy efficiency class G

light direction:



slat 40 bollard



slat 70 bollard

Artikel article	Farbe colour	Art.-Nr. item no.	Systemleistung system performance
slat 40 bollard		anthracite RAL 7016	91031-27-AN 8 W/280 lm
		space grey	91031-27-SG 8 W/280 lm
		deep black RAL 9005	91031-27-BL 8 W/280 lm
slat 70 bollard		anthracite RAL 7016	91032-27-AN 8 W/280 lm
		cool brown	91032-27-CB 8 W/280 lm
		space grey	91032-27-SG 8 W/280 lm
		deep black RAL 9005	91032-27-BL 8 W/280 lm

Zubehör accessory	Artikel article	Art.-Nr. item no.
	Erdstück anchorage unit	55099
	Y-Verbinder earth distribution box	55312

+ verwandte Produkte related products . slat . slat ceiling . slat one . slat spike

Größe in mm
size in mm