



gap Q Design: Klaus Nolting

Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h

dimmbar

Installation:
2 x Kabeleinführung;
Anschlussklemme
3 x 2,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas satiniert

Schutzart:
IP65

EEK:


light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h


dimmable

installation:
2 x cable entry point;
connection terminal
3 x 2,5 mm²











material:
aluminium die-casting
powder-coated
safety glass satined

protection class:
IP65

EEC:

Größe in mm
size in mm

| Art.-Nr. item no. | Farbe colour | Systemleistung system performance | Lichttrichtung light direction |
|----------------------|------------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------------|
| 91100-Q-AN |  anthracite RAL 7016 | 12 W/260 lm |  |
| 91100-Q-CB |  cool brown | 12 W/260 lm |  |
| 91100-Q-SG |  space grey | 12 W/260 lm |  |
| 91100-Q-WH |  pure white RAL 9016 | 12 W/260 lm |  |
| 91100-Q-BL |  deep black RAL 9005 | 12 W/260 lm |  |