



**gap Y** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

dimmbar

**Installation:**  
2 x Kabeleinführung;  
Anschlussklemme  
3 x 2,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Sicherheitsglas satiniert

**Schutzart:**  
IP65

**EEK:**



light technology:  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h


dimmable

installation:  
2 x cable entry point;  
connection terminal  
3 x 2,5 mm<sup>2</sup>

material:  
aluminium die-casting  
powder-coated  
safety glass satined

protection class:  
IP65

**EEC:**



Größe in mm  
size in mm

Art.-Nr. item no.	Farbe colour	Systemleistung system performance	Lichtrichtung light direction
91100-Y-AN	anthracite RAL 7016	12 W/210 lm	
91100-Y-CB	cool brown	12 W/210 lm	
91100-Y-SG	space grey	12 W/210 lm	
91100-Y-WH	pure white RAL 9016	12 W/210 lm	
91100-Y-BL	deep black RAL 9005	12 W/210 lm	