



**mir X 30 poller** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

dimmbar

**Installation:**  
Anschlussklemme  
3 x 2,5 mm<sup>2</sup>

**Montage:**  
Bauseitiges Fundament oder  
befestigter Untergrund

**Material:**  
Aluminiumguss  
pulverbeschichtet

**Schutzart:**  
IP65

EEK:



light technology:  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h

dimmbare


installation:  
connection terminal  
3 x 2,5 mm<sup>2</sup>

assembly:  
on site foundation or  
solid ground

material:  
aluminium die-casting  
powder-coated

protection class:  
IP65

EEC:



Größe in mm  
size in mm

| Art.-Nr.<br>item no. | Farbe<br>colour        | Systemleistung<br>system performance | Lichtrichtung<br>light direction |
|----------------------|------------------------|--------------------------------------|----------------------------------|
| 91001-AN             | anthracite<br>RAL 7016 | 12 W/240 lm                          |                                  |
| 91001-CB             | cool brown             | 12 W/240 lm                          |                                  |

**Zubehör**  
accessories

| Art.-Nr.<br>item no. | Artikel<br>article                       |
|----------------------|--|
| 55380                | <b>Abzweigkasten</b><br>distribution box |
| 55099                | <b>Erdstück</b><br>anchorage unit        |