



**shot connect** Design: Sebastian David Büscher

für festen Untergrund

for solid ground

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

**Flood Reflektor symmetrisch**

**dimmbar**

**Anschluss:**  
5m Zuleitung  
(H05RN-F 3G0,75) inkl.  
IP44.de connect Stecker

**ortsveränderlich**

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Sicherheitsglas klar

**inkl. Alu-Ring lose, ø 80 mm**

**Schutzart:**  
IP65

**EEK:**  
A+

**light technology:**  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h

**flood reflector symmetric**

**dimmable**

**connection:**  
5m supply cable  
(H05RN-F 3G0,75) incl.  
IP44.de connect plug

**movable**

**material:**  
aluminium die-casting  
powder-coated  
safety glass clear

**incl. aluminium ring loose, ø80 mm**

**protection class:**  
IP65

**EEC:**  
A+

**shot 4 W**



**Art.-Nr.**  
item no.

**Farbe**  
colour

**Systemleistung**  
system performance

**Lichtrichtung**  
light direction

91090-4W-AN-CO

**anthracite**  
RAL 7016

4 W/260 lm



91090-4W-CB-CO

**cool brown**

4 W/260 lm



**shot 15 W**



91090-15W-AN-CO

**anthracite**  
RAL 7016

15 W/980 lm



91090-15W-CB-CO

**cool brown**

15 W/980 lm

