



slat spike Design: Klaus Nolting

für unbefestigte Beet- und Grünflächen

for unpaved beds and greens

Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h

dimmbar

Anschluss:
5 m Zuleitung
(H05RN-F 3G0,75) inkl.
Schutzkontaktstecker
anschlussfertig

ortsveränderlich

Material:
Kopf: Aluminiumguss
pulverbeschichtet
Spieß: Edelstahl pulver-
beschichtet
Glas: Sicherheitsglas satiniert

Schutzart:
IP65

EEK:

light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h

dimmbable


connection:
5 m supply cable
(H05RN-F 3G0,75)
incl. safety plug
ready to connect

movable

material:
head: aluminium die-casting
powder-coated
spike: stainless steel powder-
coated
glass: safety glass satined

protection class:
IP65

EEC:



Größe in mm
size in mm

Art.-Nr. item no.	Farbe colour	Systemleistung system performance	Lichtrichtung light direction
91030-AN	anthracite RAL 7016	8 W/180 lm	
91030-CB	cool brown	8 W/180 lm	

+ Anschluss optional mit IP44.de connect. Produktdetails auf www.IP44.de.
connection with IP44.de connect as an option. product details on www.IP44.de.